

スパイラルー体物(ソリッドタイプ)

●タイプ別寸法表

Unit : mm

タイプ	カッタ平均径(呼び径)		寸 法					分割数							
	インチ	ミリ	有効刃丈	ツバ径	外径	C	高さ	C	C	C	C	C	C	C	C
A	0.50"	12.70	3.5	43	16	9	25.4/30	●	○	○					
	0.75"	19.05	3.5	43	22.5	14.5	25.4/30	●	○	○					
	0.90"	22.86	3.5	43	26	18.5	25.4/30	○	○	●					
	1.10"	27.94	3.5	43	34	24.5	25.4/30		○	●					
	1.20"	30.48	3.5	45.5	34	27	25.4/30		○	●					
	1.30"	33.02	3.5	50.5	38.35	26	25.4/30		○	●					
	1.50"	38.10	5.0	56	43	31	25.4/30		○	○	○				
	2.00"	50.80	5.0	67	57	43	25.4/30			○	○	○			
B	2.75"	69.85	7.0		77	60	27			○	○	○	○	○	
	3.00"	76.20	7.0		86	66	27			○	○	○	●	○	
	3.50"	88.90	9.5		97	71	27			○	○	○	●	○	
	3.75"	95.25	9.5		104	80	33					○	○	●	
	4.00"	101.60	9.5		112	84	33					○	○	●	
	4.50"	114.30	9.5		123	102	33					○	○	●	○
C	5.00"	127.00	9.5		135	112	50.8						○	●	○
	6.00"	152.40	9.5		160	130	50.8						○	●	○
	7.50"	190.50	13.0		200	130	50.8						○	●	○

●標準分割数

